

WALL / ON-CEILING-SPEAKER WLQ-170-DC FOR A/B SYSTEM-LINES



W
L
Q

170

D
C

F
O
R

A/B

S
Y
S
T
E
M

L
I
N
E
S

- BALL-ATTACK-PROTECTION THROUGH 2 x 1,25 MM STEEL
- VANDALISM-OPTIMIZED WITH REAR-PANEL
- 2 X PRE-EMBOSSING FOR PG-CONNECTORS
- OPTIONAL STICK-PROTECTION & TORX-SCREWS
- TOUCH-PROTECTED 100-V-QUICK-CERAMIC-CONNECTING-CLAMP
- NO BISECTION OF THE MEMBRANE-SURFACE
- IN CASE OF BREAKDOWN OF ONE LINE, CONTINUOUS FUNCTION OF THE SECOND
- TWO AUTONOMOUS VOICE-COILS PER SYSTEM
- TWO AUTONOMOUS 100-VOLT-TRANSFORMER PER SYSTEM
- IN CASE OF HEAT-OVERLOAD OF ONE VOICE-COIL, CONTINUOUS FUNCTION OF THE SECOND VOICE-COIL

TECHNICAL DATA:

	WLQ-170-DC	WLQ-170-DC/10
Loudspeaker:	5" / 2 x 15W Dual-Cone	5" / 2 x 15W Dual Cone
100-V-Power-Taps:	2 x 100V-6-3-1,5W	2 x 100V-10-5-2,5W
FO-Range:	80-17 000 Hz	80-17 000 Hz
SPL 1W/1m:	95 dB	95 dB
SPL nW/1m:	103 dB	105 dB
Dimensions:	170 x 170 x 63 mm	170 x 170 x 63 mm
Weight:	ca. 1,8 Kg	ca. 2 Kg
Colour:	white	white

