



# SPHERE-LOUDSPEAKER IN DC-VERSION FOR A/B-SYSTEM-LINES



- IN CASE OF BREAKDOWN OF ONE LINE, CONTINUOUS FUNCTION OF THE SECOND **TWO AUTONOMOUS** VOICE-COILS PER SYSTEM
- **TWO AUTONOMOUS** 100-VOLT-TRANSFORMER PER SYSTEM
- **NO BISECTION** OF THE **MEMBRANE-SURFACE**
- LOUDSPEAKER-PROTECTION THROUGH **SPECIAL VOICE-COIL-WINDINGS**
- IN CASE OF HEAT-OVERLOAD OF ONE VOICE-COIL, CONTINUOUS FUNCTION OF THE SECOND VOICE-COIL
- **NO PHASE-SHIFT** ON THE MEMBRANE-SURFACE
- FIRE-RESISTANT (METAL) / LOW FLAMMABILITY (ABS)
- **BRUSHED STAINLESS-STEEL LOOK AVAILABLE**

## TECHNICAL DATA:

	KA-180-DC	KM-180-DC / KM-180-DC-CHD
Loudspeaker:	5" / 2 x 15W-Broadband	5" / 2 x 15W-Broadband
100-V-Power-Taps:	2 x 100V-6-3-1,5W	2 x 100V-6-3-1,5W
FO-Range:	80-17 000 Hz	80-17 000 Hz
SPL 1W/1m:	95 dB	95 dB
SPL 6W/1m:	103 dB	103 dB
Radiation:	180° (1 kHz)	180° (1kHz)
Dimensions (d):	180 mm d / 155 mm (Höhe)	180 mm
Weight:	1,4 Kg	1,9 Kg
Colour:	white	white / brushed V2A-Look



S  
P  
H  
E  
R  
E  
  
K  
M  
  
1  
8  
0  
  
K  
A  
  
1  
8  
0  
  
D  
C  
  
F  
O  
R

A/B

S  
Y  
S  
T  
E  
M  
  
L  
I  
N  
E  
S