

ON-WALL/CEILING-LOUDSPEAKER DESIGN-230-DC FOR A/B-LINES



D
E
S
I
G
N

230

DC

D
E
S
I
G
N

F
O
R

- **NO LOSS OF 50% OF THE MEMBRANE-SURFACE** IN FAILURE-CASE
- IN CASE OF BREAKDOWN OF ONE LINE, CONTINUOUS FUNCTION OF THE SECOND
- **TWO AUTONOMOUS VOICE-COILS PER SYSTEM**
- IN CASE OF HEAT-OVERLOAD OF ONE VOICE-COIL, CONTINUOUS FUNCTION OF THE SECOND VOICE-COIL
- **TWO AUTONOMOUS 100-VOLT-TRANSFORMER PER SYSTEM**
- **NO PHASE-SHIFT ON THE MEMBRANE-SURFACE**
- OPTIONAL CERAMIC-CONNECTING-CLAMP & THERMO-FUSE AVAILABLE
- ONLY 2 DRILLING-POINTS FOR THE WHOLE LOUDSPEAKER
- **50-HZ-STABLE 100-V-TRANSFORMER**
- NEW SOFTLY-BENDED **DESIGN-CABINET**

TECHNICAL DATA:

DESIGN-230-DC

DESIGN-230-DC/10WATT

Loudspeaker:	5" / 2 x 15W-DUAL-Cone	5" / 2 x 15W-DUAL-Cone
100-V-Taps:	2 x 100V-6-3-1.5W	2 x 100V-10-5-2.5W
FQ-Range:	80-16 000 Hz	80-16 000 Hz
SPL 1W/1m:	95 dB	95 dB
SPL nW/1m:	103 dB	105 dB
Dimensions:	230 x 170 x 80 mm	230 x 170 x 80 mm
Weight:	1,4 Kg	1,6 Kg
Colour:	white	white

A/B

S
Y
S
T
E
M
S

