

SPHERE-LOUDSPEAKER KA-270 IN A/B & DC-EDITION



K
A
2
7
0

A/B

DC

S
P
H
E
R
E

L
O
U
D
S
P
E
A
K
E
R

- ENABLE OPERATION OF SPEAKER VIA **TWO DISCRETE CABLE-LINES**
- IN CASE OF BREAKDOWN OF ONE LINE, CONTINUOUS FUNCTION OF THE SECOND
- **TWO AUTONOMOUS** 100-VOLT-TRANSFORMER PER SYSTEM
- **TWO AUTONOMOUS** LOUDSPEAKER PER SYSTEM (KA-270-AB)
- **TWO AUTONOMOUS** VOICE-COILS PER SYSTEM (DC)
- **NO BISECTION** OF THE **MEMBRANE-SURFACE** (KA-270-DC)
- **NO PHASE-SHIFT** ON THE MEMBRANE-SURFACE
- 50-HZ-STABLE TRANSFORMER
- **5 METER** CABLE WITH STEEL-CORE
- METAL-FRONTGRILL

TECHNICAL DATA:

	KA-270-DC	KA-270-AB
Loudspeaker:	6,5" / 2 x 15W Dual-LS	2 x 15W 165mm x 70mm Fullrange
100-V-Power-Taps:	2 x 100V-6-3-1,5W	2 x 100V-6-3-1,5W
100-V-optional:	2 x 100V-10-5-2,5W	2 x 100V-10-5-2,5W
FQ-Range:	80-17 000 Hz	70-20 000 Hz
SPL 1W/1m:	95 dB	93 dB
SPL 6W/1m:	103 dB	101 dB
Dimensions (d):	270 mm d / 230 mm	270 mm d / 230 mm
Weight:	ca. 1,8 Kg	ca. 1,8 Kg
Material:	ABS / Metal	ABS / Metal
Colour:	white	white

