

CLB-220-II-WAY-30-WATT Ceiling-Speaker in full-metal-design



**C
L
B**

220F

**II
WAY**

**30
WATT**

- HIGH-SPL-2-WAY-LOUDSPEAKER-SYSTEM FOR ADVANCED APPLICATIONS
- FIRE-RESISTANT/PROTECTED CABINET
- EASY-MOUNTING THROUGH FAST-SPRING/BAYONET-SYSTEM
- 50-HZ-STABLE 100-V-TRANSFORMER
- TOUCH-PROTECTED 100-V-QUICK-CONNECTING-CLAMP
- OPTIONAL CERAMIC-CONNECTING-CLAMP & THERMO-FUSE AVAILABLE
- POWER-SAVING THROUGH **HIGH SOUND-PREASURE-LEVEL**
- OPTIONAL **FIRE-DOME** & **IN-WALL/CONCRETE-DOME** AVAILABLE
- **BALL-PROOF-VERSION** ACCORDING TO DIN 18032/III AVAILABLE

HIGH

SPL

TECHNICAL DATA:

CLB-220-II-WAY/30WATT

Loudspeaker:	30-Watt-II-Way-System
Power-Consumption:	100V-30-20-10-6-3W
Frequency-Range:	70-20 000 Hz
SPL 1W/1m:	97 dB
SPL 10W/1m:	111,5 dB
Dimensions:	220 mm x 105 mm
Ceiling-Cut-Out:	200 mm
Weight:	1,7 Kg
Colour:	white

**C
E
I
L
I
N
G**

**L
O
U
D
S
P
A
E
K
E
R**

