


ALU-COLUMN-SPEAKER 20/40/60/80-WATT SLIM-20-40-60-80



S
L
I
M

20
40
60
80


A
L
U

ROUND

- ROUND ALU-CASING WITH METAL-FRONT-GRILL
- ONLY 76-MM-DIAMETER
- SPLASH-WATER-PROTECTED
- INNER-ALU-PANEL
- MOUNTING-BRACKET INCLUDED
- COLOUR SIMILAR TO 9003 & 9016
- HIGH SPEECH-INTELLIGIBILITY
- SCREWED-CABLE-GLAND

TECHN. DATA:	SLIM-20	SLIM-40	SLIM-60	SLIM-80
--------------	---------	---------	---------	---------

Loudspeaker:	4 x 2" Broadband	8 x 2" Broadband	12 x 2" Broadband	16 x 2" Broadband
Power-Taps:	100V-20-10W	100V-40-20W	100V-60-30W	100V-80-40W
FO-Range:	250-18 000 Hz	200-18 000 Hz	180-18 000 Hz	150-18 000 Hz
SPL 1W/1m:	94 dB	96 dB	97 dB	98 dB
SPL NW/1m:	107 dB	112 dB	1115 dB	116 dB
Dimensions (HxBxT)	340x76x100	560x76x100	780x76x100	990x76x100
Weight:	1,7 Kg	2,6 Kg	3,5 Kg	4,4 Kg
Colour:	white	white	white	white



SLIM-80




SLIM-60



Page-75



SLIM-40



SLIM-20

