

DLS-265-AB & WHL-250-AB with 2 discrete System-Lines A / B



W
H
L

250
A/B

D
L
S

265
A/B

- **TWO AUTONOMOUS** LOUDSPEAKER PER SYSTEM
- **TWO AUTONOMOUS** 100-VOLT-TRANSFORMER PER SYSTEM
- ENABLE OPERATION OF SPEAKER VIA TWO DISCRETE CABLE-LINES
- IN CASE OF FAILURE OF ONE LINE, CONTINUOUS FUNCTION OF THE SECOND-LINE
- **50-HZ-STABLE** 100-V-TRANSFORMER
- **TOUCH-PROTECTED** 100-V-QUICK-CONNECTING-CLAMP
- OPTIONAL CERAMIC-CONNECTING-CLAMP & THERMO-FUSE AVAILABLE
- **CUSTOM COLOUR & WEATHER-PROOF**-VERSIONS OPTIONAL (DLS)
- OPTIONAL RG-220F / LAMPRODYN-200 / SZ-20-WA IN AB-VERSION

A / B

TECHNICAL DATA:

	DLS-265-AB	WHL-250-AB
Loudspeaker:	2 x 15W 165 x 70-mm-Fullrange	2 x 15W 165 x 70-mm-Fullrange
Power-Consumption:	100V-6-3-1,5W or 10-5-2,5W	100V-6-3-1,5W or 10-5-2,5W
Frequency-Range:	70-20000 Hz	70-20000 Hz
SPL 1W/1m:	93 dB	93 dB
SPL 6W/1m:	101 dB	101 dB
Dimensions:	265 mm x 90 mm cutout/:240mm	255 x 195 x 85 mm
Weight:	2 Kg	2,2 Kg
Material:	Metal	MDF / Metal-Grill
Colour:	White RAL 9010	white
optional:	Firedome FT-265F	

S
Y
S
T
E
M

L
I
N
E
S

