

# 6/10-Watt on-wall-loudspeaker WHL-250G with rear-panel

W  
H  
L  
  
250G



W  
A  
L  
L

- VERY FAST MOUNTING THROUGH **QUICK-SNAP-REAR-PANEL**
- ONLY 2 DRILLING-POINTS FOR THE WHOLE LOUDSPEAKER
- HIGHLY **STABLE** MDF-CABINET OF VERY LOW **FLAMMABILITY**
- **50-HZ-STABLE** 100-V-TRANSFORMER
- **TOUCH-PROTECTED** 100-V-CONNECTING-CLAMP
- BALL-ATTACK-RESISTANT FRONT-GRILL
- POWER-SAVING THROUGH HIGH **SOUND-PREASURE-LEVEL**
- VOLUME-CONTROL & **24-V-RELAY** INCL. ASSEMBLING OBTAINABLE

O  
N

L  
O  
U  
D  
S  
P  
E  
A  
K  
E  
R

## TECHNICAL DATA:

### WHL-250G/6WATT

### WHL-250G/10WATT

Loudspeaker:	15W/165mm-broadband	15W/165mm-broadband
Power-Consumption:	100V-6-3-1.5W	100V-10-5-2.5W
FO-Range:	80-17000 Hz	80-17 000 Hz
SPL 1W/1m:	96 dB	96 dB
SPL 6W/1m:	104 dB	106 dB
SPL max 1W/1m:	98,5 dB (1,8kHz)	98,5 dB (1,8kHz)
SPL max 6W/1m:	106,5 dB (1,8kHz)	108,5 dB (1,8kHz)
Radiation:	160° (1kHz)	160° (1kHz)
Dimensions:	255 x 195 x 85 mm	255 x 195 x 85 mm
Weight:	1,8Kg	1,9 Kg
Colour:	white	white

