

# Quadratic-ball-protected-full-metal-wall/ceiling-loudspeaker **WLO-160F**



**W  
L  
O  
160F**

**B  
A  
L  
L  
P  
R  
O  
T  
E  
C  
T  
E  
D  
-  
V  
A  
N  
D  
A  
L  
I  
S  
M  
O  
P  
T  
I  
M  
I  
Z  
E  
D**

- **BALL-ATTACK-PROTECTION** THROUGH 1,5 MM STEEL
- **VANDALISM-OPTIMIZED**
- OPTIONAL STICK-PROTECTION & **TORX-SCREWS**
- **50-HZ-STABLE** 100-V-TRANSFORMER
- **TOUCH-PROTECTED** 100-V-QUICK-CONNECTING-CLAMP
- SPEECH-OPTIMIZED-LOUDSPEAKER-QUALITY
- VOLUME-CONTROL & **24-V-RELAY** AVAILABLE
- CUSTOM-SIZE & STAINLESS-STEEL-VERSIONS OBTAINABLE
- **WEATHER-PROOFED** & WEATHER-PROTECTED-VERSION AVAILABLE

## TECHNICAL DATA:

	WLO-160F	WLO-230F (OPTIONAL)
Loudspeaker:	6W/100mm-broadband	10/15W broadband with HF-dome
Power-Consumption:	100V-6-3-1,5W	100V-6-3-1,5W
FO-Range:	80-15 000 Hz	70-18 000 Hz
SPL 1W/1m:	92 dB	95 dB
SPL 6W/1m:	100 dB	103 dB
Radiation:	180 ° (1,4 kHz)	180° (0,9 kHz) 160° (1 KHz)
Dimensions:	160 x 160 x 70 mm	230 x 230 x 100 mm
Weight:	1,8 Kg	2,5 Kg ca.
Colour:	RAL 9010	on demand

