

6-W-sphere-loudspeaker KL-180F / KL-250F in full-metal-design



K
L
180F
250F

6
W
A
T
T
S
P
H
E
R
E
L
O
U
D
S
P
E
A
K
E
R

- FIRE-RESISTANT/PROTECTED
- AGELESS FORM-STABLE
- **50-HZ-STABLE** 100-V-TRANSFORMER
- OUTSTANDING LOUDSPEAKER-QUALITY (DLS-180/220F)
- POWER-SAVING THROUGH HIGH SOUND-PREASURE-LEVEL
- CUSTOM-COLOUR & **CHROME-PLATED** VERSIONS OBTAINABLE
- **2-WAY** & 8-OHM & **10-20-30-WATT**-VERSIONS AVAILABLE
- **CUSTOM-VERSIONS** IN ALL KINDS OBTAINABLE
- DIFFERENT **CABLE-LENGTHS** WITH STEEL-CORE AVAILABLE

TECHNICAL DATA:

	KL-180F/6W	KL-250F/6W
Loudspeaker:	6W/120mm-broadband	10/15W-160mm broadband with HF-dome
Power-Consumption:	100V-6-3-1.5W	100V-6-3-1.5W
FQ-Range:	80-15 000 Hz	70-18 000 Hz
SPL 1W/1m:	94 dB	95 dB
SPL 6W/1m:	102 dB	103 dB
SPL 1W/1m max:	100 dB (1,5kHz)	102 dB (3,2 kHz)
SPL 6W/1m max:	108dB (1,5kHz)	110 dB (3,2 kHz)
Radiation:	360 ° (1,0kHz)	360° (1,0 kHz)
Dimensions (dia)	180 mm	252 mm
Weight:	ca. 1,5 Kg	ca. 2,5 Kg
Colour:	RAL 9010	RAL 9010

