

CLB-220-DUAL-CONE & WHL-250-DUAL-CONE for A/B-SYSTEM-LINES



CLB
220
DUAL
CONE

WHL
250
DUAL
CONE

- NO LOSS OF 50% OF THE MEMBRANE-SURFACE IN FAILURE-CASE
- IN CASE OF BREAKDOWN OF ONE LINE, CONTINUOUS FUNCTION OF THE SECOND
- TWO AUTONOMOUS VOICE-COILS PER SYSTEM
- TWO AUTONOMOUS 100-VOLT-TRANSFORMER PER SYSTEM
- LOUDSPEAKER-PROTECTION THROUGH SPECIAL VOICE-COIL-WINDINGS
- 60-WATT-PEAK-POWER-RATING PER VOICE-COIL
- IN CASE OF HEAT-OVERLOAD OF ONE VOICE-COIL, CONTINUOUS FUNCTION OF THE SECOND VOICE-COIL
- NO PHASE-SHIFT ON THE MEMBRANE-SURFACE
- OPTIONAL CERAMIC-CONNECTING-CLAMP & THERMO-FUSE AVAILABLE
- OPTIONAL 10-W / LAMPRODYN / RG & SPHERE-VERSIONS AVAILABLE

A / B

S
Y
S
T
E
M
E

L
I
N
E
S

TECHNICAL DATA:	CLB-220-DC	WHL-250-DC
Loudspeaker:	6,5" / 2 x 15W with HF-Cone	6,5" / 2 x 15W with HF-Cone
100-V-Taps:	2 x 100V-6-3-1.5W	2 x 100V-6-3-1.5W
Frequency-Range:	70-18 000 Hz	70-18 000 Hz
SPL 1W/1m:	95 dB	95 dB
SPL 6W/1m:	103 dB	103 dB
Dimensions:	220 mm x 95 mm/cutout: 200 mm	255 x 195 x 85 mm
Weight:	1,7 Kg	2,2 Kg
Material:	Metal	MDF / Metal-Grill
Colour:	white / opt. custom-colour	white
optional 100-Volt:	2 x 100V-10-5-2,5W	2 x 100V-10-5-2,5W
optional:	FIREHOME FT-220F / Damp-Room-Version	

