

# 100-Volt-30W-20W-Monitor-Loudspeaker for Wall / Ceiling-Mounting



**ML  
200**

**ML  
260**

**C  
O  
M  
P  
A  
C  
T  
  
M  
O  
N  
I  
T  
O  
R**

- AGELESS FORM-STABLE
- EASY-MOUNTING THROUGH OMNI-MOUNT-BRACKET
- **50-HZ-STABLE** 100-V-TRANSFORMER
- **TOUCH-PROTECTED** 100-V-QUICK-CONNECTING-CLAMP
- SELECTED LOUDSPEAKER-QUALITY
- QUICK-**IMPEDANCE-CHANGE** THROUGH REAR-PANEL-ROTARY-SWITCH
- STANDARD-COLOURS BLACK & WHITE
- CUSTOM-COLOURS AVAILABLE (QUANTITY-RELATED)

## TECHNICAL DATA:

	ML-200 BLACK/WHITE	ML-260 BLACK/WHITE
Loudspeaker:	2-Way-System	2-Way-System
Power-Consumption:	100V-20-15-7,5-3,75W switchable to 8 Ohm	100V-30-15-7,5-3,75W switchable to 8 Ohm
FO-Range:	80-20 000 Hz	60-20 000 Hz
SPL 1W/1m:	90 dB	92 dB
SPL nW/1m:	102 dB	107 dB
Dimensions:	220 x 160 x 140 (160) mm	245 x 180 x 165 (185) mm
Weight:	1,9 Kg	2,6 Kg
Material:	ABS	ABS
Colour:	black & white	black & white

**8 OHM**

**&**

**100-VOLT**

