



HYPERSONIC
10
12
15

PA

SPEAKER

SYSTEM

- **SCRATCH-RESISTANT** BASS-REFLEX-PLASTIC-ENCLOSURE
- HIGH-CLASS COMPONENTS FOR **MUSIC-PERFORMANCE**
- **BUILT-IN STAND-FLANGE**
- SIDE-INTEGRATED CARRY-HANDLE
- **OPTIONAL AVAILABLE:**
- **100-V-HIGH-END-RING-CORE-TRANSFORMER** OR **STANDARD-TRANSFORMER**
- HEIGHT-ADJUSTABLE **SPEAKER-STAND**
- WALL-MOUNTING BRACKET WITH OPTIONAL STABILIZATION BRACKET

TECHNICAL DATA:	HYPERSONIC-10	HYPERSONIC-12	HYPERSONIC-15
Components:	10"LF / 1,25"HF-Driver	12"LF / 1,25"HF-Driver	15"-LF/1,75"HF-Driver
Impedance:	8 Ohms	8 Ohms	8 Ohms
Nominal Power:	200W	300W	300W
Frequency-Range:	55-20 000 Hz	50-20 000 Hz	40-20 000 Hz
SPL 1W/1m:	94 dB	96 dB	96 dB
SPL nW/1m:	117 dB	121 dB	121 dB
Dimensions:	510 x 341 x 280 mm	580 x 410 x 330 mm	690 x 470 x 410 mm
Weight:	11 Kg	16 Kg	22 Kg
Colour:	black	black	black
Connectors:	Speakon & 6,3 Jack	Speakon & 6,3 Jack	Speakon & 6,3 Jack
optional 100-Volt:	100V-200-150-100W	100V-200-150-100W	100V-200-150-100W
optional 100-Volt:	100V-100-75-50W	100V-100-75-50W	100V-100-75-50W

