

Weatherproof aluminium-sound-columns 10/20/30/40/50W

SZ-10WA

SZ-20WA

SZ-30WA

SZ-40WA

SZ-50WA

S
O
U
N
D



- WEATHER-PROOF THROUGH EXCLUSIVE-USE OF ALUMINIUM-COMPONENTS
- STEAM/DAMPNESS-PROTECTED & DUST-PROTECTED
- BALL-ATTACK PROTECTED TRAPEZOID CASING
- BALL-ATTACK-PROTECTED MOUNTING-BRACKET
- 100-VOLT-1-1/2-POWER-TAPS
- CUSTOM-COLOUR AVAILABLE
- ALL SZ-WA-MODELS ALSO IN RAL 9010 AVAILABLE



TECHN. DATEN:	SZ-10WA	SZ-20WA	SZ-30WA	SZ-40WA	SZ-50WA
Nominal Power:	10Watt	20Watt	30Watt	40Watt	50Watt
Power Consumption:	100V-10-5W	100V-20-10W	100V-30-15W	100V-40-20W	100V-50-25-12,5W
FQ-Range:	100-15000 Hz	90-16000 Hz	85-16000 Hz	80-16000 Hz	70-18000 Hz
SPL 1W/1m:	95 dB	98 dB	99 dB	100 dB	101 dB (HE-transf)
SPL 1W/1m:	105 dB	111 dB	114 dB	116 dB	118 dB
Dimensions (h>xwxd):	320x147x110mm	370x147x110mm	510x147x110mm	610x147x110mm	610x147x110mm
Weight:	3 Kg	3,5 Kg	4 Kg	5 Kg	6 Kg
Colour:	black & RAL 9010	black & RAL 9010	black & RAL9010	black & RAL9010	black & RAL 9010

W
E
A
T
H
E
R
P
R
O
O
F

