

6-watt-acoustic-panel-loudspeaker 300 x 300 mm SW-E11 / E21/ E31

SW

E11

E21

E31



A
C
O
U
S
T
I
C

P
A
N
E
L

L
O
U
D
S
P
E
A
K
E
R

- **DUST-PROTECTION & FOAM-RUBBER-ANTI-VIBRATION-STRIPES** STANDARD
- **50-HZ-STABLE** 100V-TRANSFORMER
- **TOUCH-PROTECTED-QUICK-CONNECTING-CLAMP**
- ADDITIONAL MOUNTING-DEVICE & **STRAIN-RELIEF** AVAILABLE
- **OUTSTANDING** LOUDSPEAKER-QUALITY FOR MUSIC / SPEECH
- POWER-SAVING THROUGH HIGH **SOUND-PREASURE-LEVEL**
- **LOW-COST-VERSION** WITHOUT DUST-COVER OBTAINABLE
- CUSTOM-COLOUR & CUSTOM-SIZE-VERSIONS AVAILABLE
- **2-WAY & 10-20-30-WATT & 8-OHMS-VERSIONS** OBTAINABLE
- **FIRE-RESISTANT & WEATHER-PROOF-VERSIONS** AVAILABLE

TECHNICAL DATA:

	SW-E11	SW-E21	SW-E31
Loudspeaker:	6W/120mm-broadband	10/15W broadband With HF-dome	10/15W-broadband with HF-dome
Power-Consumption:	100V-6-3-1.5W	100V-6-3-1.5W	100V-6-3-1.5W
FQ-Range:	80-15 000 Hz	70-18 000 Hz	70-19000Hz
SPL 1W/1m:	94 dB	95 dB	98 dB
SPL 6W/1m:	102 dB	103 dB	106 dB
SPL 1W/1m max:	104 dB (3,5 kHz)	106 dB (3,2 kHz)	105 dB (3,8 kHz)
SPL 6W/1m max:	112 dB (3,5 kHz)	114 dB (3,2 kHz)	113dB (3,8 kHz)
Radiation:	180° (1,8 kHz)	180° (1,5 kHz)	180° (1,4 kHz)
Dimensions:	300 x 300 x 55 mm	300 x 300 x 70 mm	300 x 300 x 80 mm
Weight:	1 Kg	1,2 Kg	1,3 Kg
Front-Colour:	RAL 9005	RAL 9005	RAL 9005
Material:	wood	wood	wood

