

WALL / ON-CEILING-SPEAKER RG-220-AB & RG-180-DC for A/B-LINES



RG  
220  
A/B  
  
RG  
180  
DC  
  
A / B

- **TWO AUTONOMOUS** LOUDSPEAKER PER SYSTEM (RG-220-AB)
- **TWO AUTONOMOUS** VOICE-COILS PER SYSTEM (RG-180-DC)
- **TWO AUTONOMOUS** 100-VOLT-TRANSFORMER PER SYSTEM
- ENABLE OPERATION OF SPEAKER VIA TWO DISCRETE CABLE-LINES
- IN CASE OF FAILURE OF ONE LINE, CONTINUOUS FUNCTION OF THE SECOND-LINE
- **50-HZ-STABLE** 100-V-TRANSFORMER
- **TOUCH-PROTECTED** 100-V-QUICK-CONNECTING-CLAMP
- OPTIONAL CERAMIC-CONNECTING-CLAMP & THERMO-FUSE AVAILABLE
- **CUSTOM COLOUR & WEATHER-PROOF-VERSIONS** OPTIONAL

L  
S  
  
S  
Y  
S  
T  
E  
M  
  
L  
I  
N  
E  
S

TECHNICAL DATA:	RG-220-AB	RG-180-DC
Loudspeaker:	2 x 15W 165 x 70-mm-Fullrange	6,5" / 2 x 15W with HF-Cone
100-V-Taps:	2 x 100V-6-3-1.5W	2 x 100V-6-3-1.5W
FO-Range:	80-20 000 Hz	80-16 000 Hz
SPL 1W/1m:	93 dB	95 dB
SPL 6W/1m:	101 dB	103 dB
Dimensions:	220 mm x 100 mm	180 x 70 mm
Weight:	1,40 Kg	1,80 Kg
Material:	Metal	Metal
Colour:	RAL 9010	RAL 9010
optional:		Ball-ATTACK-Certificated-Version

