

100V/10W-CLB-220-II-WAY-Ceiling-Speaker in full-metal-design



CLB
220F
II
WAY
HIGH

S
P
L
C
E
I
L
I
N
G
L
O
U
D
S
P
E
A
K
E
R

- HIGH-SPL-2-WAY-LOUDSPEAKER-SYSTEM FOR ADVANCED APPLICATIONS
- FIRE-RESISTANT/PROTECTED CABINET
- EASY-MOUNTING THROUGH FAST-SPRING/BAYONET-SYSTEM
- **50-HZ-STABLE** 100-V-TRANSFORMER
- **TOUCH-PROTECTED** 100-V-QUICK-CONNECTING-CLAMP
- OPTIONAL CERAMIC-CONNECTING-CLAMP & THERMO-FUSE AVAILABLE
- POWER-SAVING THROUGH **HIGH SOUND-PREASURE-LEVEL**
- OPTIONAL **FIREDOME** & **IN-WALL/CONCRETE-DOME** AVAILABLE
- **BALL-PROOF-VERSION** ACCORDING TO DIN 18032/III AVAILABLE

TECHNICAL DATA: CLB-220-II-WAY

Loudspeaker:	10/15W-II-Way-System
Power-Consumption:	100V-10-5-2,5W
Frequency-Range:	70-20 000 Hz
SPL 1W/1m:	96 dB
SPL 10W/1m:	106 dB
Dimensions:	220 mm x 100 mm
Ceiling-Cut-Out:	200 mm
Weight:	1,3 Kg
Colour:	white

